



FILTERMATIC 2 SKID

- Reduce fresh water consumption by 70% or more
- Saves on sewer and chemical costs
- Includes SOBRITE® proven odor control
- UL listed control panel
- Long term cost effective solution

FILTERMATIC 2 RECLAIM SYSTEM 30 SERIES SKID

SPECIFICATIONS:

- 3 Phase 208-240/480 fla 32-29/15
- 120 VAC 20 amp Control Circuit
- Patented SOBRITE AquaPrep odor control technology
- Electric - 60Hz
- 3/4" Compressed Air 90 psi @ 10cfm
- Skid-Mounted (Pre-Wired, Pre-Plumbed)

AQUAPREP:

- TEFC Motor - 2 HP
- Flow Rate - 50 GPM
- Suction - 2"
- Discharge - 2"
- 24-Hour Clock Timer
- Operation Modes - Manual/Off/Automatic

FILTER PUMP:

- TEFC Motor - 7.5 HP
- Pump - Closed Impeller
- Flow Rate - 60-140 GPM
- Suction - 3"
- Discharge - 2"
- Backwash - 2"
- Operation Modes - Manual/Off/Automatic

DIMENSIONS:

- Filtermatic 2 Skid - 48"L x 40"W x 74"H
- Vessel #1 & 2 - 38"Ø x 88"H



SOBRITE®

WATER TREATMENT SOLUTIONS:

A leader in water treatment solutions for over 40 years, SOBRITE uses the latest technology to design and manufacture water reclaim systems, spot-free water units, water softeners, and proven odor control systems.

WHAT SETS SOBRITE® APART:

1. Good re-use water that does not smell.
2. Customer support before and after sale.
3. Low annual maintenance costs.