



# Reclaim System

## **FILTERMATIC 2 SKID FILTERMATIC RECLAIM SYSTEM 40 SERIES SKID**

### **SPECIFICATIONS**

- 208-230/460 VAC 3PH 60Hz
- 120 VAC 20 amp Control Circuit
- Patented SOBRITE® AquaPrep Odor Control Technology
- 3/4" Compressed Air 90psi @ 10cfm Required
- Skid-Mounted (Pre-Wired, Pre-Plumbed)

### **AQUAPREP**

- TEFC Motor: 2 HP
- Flow Rate: 50 GPM
- Suction: 2"
- Discharge: 2"
- 24-Hour Clock Timer
- Operation Modes: Hand/ Off / Auto

### **FILTER PUMP**

- TEFC Motor: 7.5 HP
- Pump: Closed Impeller
- Flow Rate: 60-140 GPM
- Suction: 3"
- Discharge: 2"
- Backwash: 2"
- Operation Modes: Hand / Off / Auto

### **DIMENSIONS**

- Filtermatic 2 Skid: 48"L x 40"W x 74"H
- Vessel 1 & 2: 38"Dia x 88"H

- Reduce Fresh Water Consumption by 70% or More
- Saves on Sewer and Chemical Costs
- Includes SOBRITE® Proven Odor Control
  - UL Listed Control Panel
- Long-Term Cost Effective Solution



(DESIGN SUBJECT TO CHANGE)

### **SOBRITE®**

### **WATER TREATMENT SOLUTIONS**

A leader in water treatment solutions for over 40 years, SOBRITE® uses the latest technology to design and manufacture water reclaim systems, spot-free water units, water softeners, and proven odor control systems.

#### **WHAT SETS SOBRITE® APART:**

1. Good Re-Use Water That Does Not Smell
2. Customer Support Before and After Sale
3. Low Annual Maintenance Costs

